



IIM NAGPUR

भारतीय प्रबंध संस्थान नागपुर
Indian Institute of Management Nagpur

IIMN/113/2022-23/007 dated 08/04/2022

INDIAN INSTITUTE OF MANAGEMENT NAGPUR



TENDER DOCUMENT

**Supply Installation and commissioning of Kitchen Equipment for
Executive Education Dining for IIM Nagpur MIHAN Campus.**

Part-1 Technical bid

Client

CAO

Indian Institute of Management Nagpur – 440010

Email : purchase@iimnagpur.ac.in

Phone no. 7875832307/7030937782



NOTICE INVITING TENDER (Offline mode)

Tender no: Ref. No. IIMN/113/2022-23/007 Dated 08/04/2022

1. Bids are invited under two bid system for **Supply Installation and commissioning of Kitchen Equipment's for Executive Education Block Dining for IIM Nagpur MIHAN Campus** (hereinafter to be referred as "IIMN"). The bids are to be submitted in a sealed envelope as per the timelines below. Tender Document is available on IIMN Website- www.iimnagpur.ac.in/tenders/

Bid Publishing Date	08/04/2022
Last date of Bid Submission	29/04/2022; by 11.00 AM
Technical Bid Opening Date	29/04/2022; at 11.30 AM
Financial Bid Opening Date – Price Bids of only those bidders whose Technical Bids are complete in all respects will be opened.	29/04/2022 at 03.00 PM (May be changed if technical bid evaluation is delayed)

Sealed Bids (with the Tender No. clearly written on the envelope) should reach at the below address before the last date:

IIM Nagpur Plot No.1,
Sector 20,
MIHAN
Nagpur - 441108

Chief Administrative officer
Indian Institute of Management
Nagpur



Chapter 1

PART 1 – Technical Bid		
Sealed bids are invited from bonafide, experienced & reputed dealers of financial standing for the job given below:		
101	Name of work	Supply Installation and commissioning of Kitchen Equipment for EXECUTIVE EDUCATION BLOCK Dining for IIM Nagpur MIHAN Campus
102	Reference no.	Tender no: IIMN/113/2022-23/007 Dated 08/04/2022
103	Details of bidder	Annexure A to be filled, signed and stamped and submitted with the bid.
104	Tender fees	Nil
105	Tender processing fees	Nil
106	Earnest Money Deposit (EMD)	A Bid Security Declaration is to be submitted by the bidder in lieu of EMD. The format (Attached as Annexure B) shall be printed on the bidder's letterhead, signed and stamped by the authorized signatory and submitted with the PQ & Technical Bid.
107	Contract Period	4 weeks from the date of issue of Purchase order OR date of approval by Institute authority (Whichever is later). Extendable for the reasons beyond contractor's control and upon institute's recommendation.
108	Liquidated Damage	Delivery shall be considered complete when full quantities of all items are in fully functional condition at designated delivery location as per the instruction of the representative of IIMN. For late delivery (LD) the liquidity damage shall be @1% of the contract amount per week delay. Maximum up to 5%. Beyond 5 weeks of delay in delivery, the order will be deemed cancelled.
109	Initial Security Deposit (ISD)	Initial security deposit (ISD) @ 3% of the Contract Value to be paid within One week of award of contract.
110	Interest on Security Deposit	No interest will be paid on any deposit
111	Release of ISD	On completion of defect liability period
112	Defect Liability Period	12 months from the date of installation of all the items of the contract and certified by IIMN authorities.



113	Conditional Bids	Conditional bids or Bids based on the process / basic schemes other than mentioned and / or not conforming to the technical specifications / requirements of the Bidding documents will not be considered.
114	Insurance	The bidders have to take the responsibility of its manpower & material. For any incidental loss IIM Nagpur will not be held responsible. The successful bidder has to indemnify IIMN for any consequential loss arising out of any negligent act.
115	Work and risk cost	The Institute reserves the right to get the whole or part of the order executed by some other agency at the risk and cost of the contractor if it is found that the quality and/or the progress in respect of whole or part of the supply is not satisfactory.
116	Indemnity	The Contractor shall keep the Institute indemnified against all losses and claims for injuries and or damages to any person or property. The contractor shall abide by and observe all statutory laws and regulations and shall keep the Institute indemnified against all penalties and liabilities of every kind for breach of any such statute ordinance or law/regulations or bylaws.
117	Compliance with owners' rules and regulations	The Contractor shall comply with all norms stipulated by the Owner such as Gate Passes, Checking, Maintenance of Cleanliness, Discipline & Decency at and Around the work site, Safety Precautions and Safety Regulations.
118	Arbitration	All disputes regarding quality, specifications and rates shall be tried to be settled mutually by making references to conditions of contract documents or prevailing local practices, etc., but if not settled mutually, shall be referred to arbitration subject to relevant Arbitration and Conciliation Act 1996. and its amendments, modifications to-date. Arbitration cost to be shared equally by the owner and the contractor.
119	Prices, Taxes & Duties	The Bidder should quote firm prices/ rates inclusive of all charges and expenditure required to be incurred by him/her for supply and installation of items as per the bid document. Please mention GST % and Rates including GST in the Price bid. No additional payment will be made. Price Bids are to be filled in the given format only.
120	Bid Validity	The bid submitted by bidder shall remain valid for a period of THREE Months from the date of opening of offer. Bidder shall not be entitled during this period to revoke or vary the content of Bid or any term thereof. In such case of making any variation subsequent to submission of bid at their own, the offer shall be treated as "REJECTED."
121	Award of similar type of work on same rates	Upon mutual consent, the client may award Purchase order for the items in this tender based on these rates, for which the rates may be valid up to 1 year from the date of issue of Purchase Order.



122	Rejection of bid(s)	The Owner reserves the right to reject any or all the tenders relating to the work under this Tender Document without assigning any reason whatsoever.
123	Quantum of work	The quantities given in the "SCHEDULE OF QUANTITIES" (Part-2, Price Bid) are approximate only and may vary at the time of issue of Purchase Order. The bidder is therefore, advised to quote very carefully. No claim for compensation from the Contractor shall be entertained due to any variation in quantities (irrespective of the quantum of variation) OR deletion of any item. The rates fixed for the contract shall remain same throughout the contract period. Actual executed quantities shall be measured and paid.
124	Assignment and sub-contracting	The Contractor shall not assign, sub-contract or sub-let the whole or any part of the contract in any manner. In case of on unavoidable circumstances, the contractor shall be able to do it with approval of the owner of premises. However, the job shall be sublet only to the party approved by the owner.
125	Interpretation	The Special conditions of Contract shall be read in conjunction with all other documents forming this contract. Notwithstanding the subdivisions of the documents into these separate sections, every part of each shall be deemed to be supplementary to and complimentary of every part and shall be read with the complete contract document.
126	Delivery	The delivery will be considered complete when all the items as per Purchase Order are supplied and installed at the Institute's premises and inspected by the institute authority.
127	Payment of Bills	Payments will be made within 21 days of submission of invoice provided the invoice is complete and duly authenticated by the institute authority after completion of the work in all respect.
128	Escalation / De-escalation of rates	Prices/Rates quoted will be firm during the entire duration of contract.
129	Force Majeure	If the whole of any part of the performance by the Parties of any part of their respective obligations hereunder is prevented or delayed by causes, circumstances or events beyond the control of the Parties including delays due to floods, fires, accidents, earthquakes, riots, explosions, wars, hostilities, acts of government, custom barriers, or other causes of like character beyond the control of the Parties, then to the extent the Parties shall be prevented or delayed from performing all or any part of its obligations hereunder by reason thereof despite due diligence and reasonable efforts to do so notwithstanding such causes, circumstances or events, the Parties shall be excused from performance hereunder for so long as such causes, circumstances or events shall continue to prevent or delay such performance.



130	Mathematical error	During the opening of price bids, the total quoted amount will be declared. However, during calculation verification if there is any error found in total amount, the agency will be called for clarifications. The rates quoted by the agency will be considered firm and hence the amount will be worked out by multiplying the rate with quantity. The rate will not be allowed to be changed in any case. However, decision by Asst. Manager (A&C), IIMN on the interpretation of the entire contract terms and conditions will be final and binding to all.
131	Award of Contract	The Overall lowest bidder will be awarded the contract.
132	Undertaking	The bidder has to attach an undertaking on the letterhead of the company that they have not been blacklisted by any organization.
133	Bid format	The bid shall be submitted in 2 separate envelope in the order as follows.
133.1	Sealed Envelope - 1	Technical BID -Legible copies of documents mentioned in duly self-attested by bidder to be submitted along with the PQ BID documents as per chapter 2 and document checklist, Tender documents as issued from IIMN office or download from IIMN website to be submitted and must be stamped with bidder's seal & signature on each page.
133.2	Sealed Envelope - 2	Price bid -documents downloaded from IIMN website to be filled and signed with bidder's seal.



Chapter 2

Eligibility Criteria for Bidders:

Sr.	Description	Remarks (Documents to be attached)
1	Bidder must be authorized enlisted supplier/distributor of designated brands.	Please attach proof of authorized dealership.
2	Bidder must be in the business of supply of kitchen equipment and appliances as per the items in Scope of work for at least five years.	Please attach proof of establishment of business and dealership.
3	The annual turnover of the bidder in last three consecutive financial years as on 31.03.2020 (For FY 2018-19, 2019-20 & 2020-21) shall be minimum Rs: 25 lakh	Please attached Chartered Accountant's certificate / Signed copies of audited accounts (Balance sheet & Profit and loss accounts) duly certified by the Chartered Accountant. Fill in Annexure C
4	Bidder should not have been blacklisted to supply from any government organization.	An undertaking on the Bidder's letterhead to that effect should be attached with the Technical Bid.

Desirable Conditions –

1. The bidder should have a dealership / business office in Nagpur





Chapter 3
Scope of Work



Supply, Installation and commissioning of Kitchen Equipment for Executive Education Block Dining for IIM Nagpur MIHAN Campus.

The Kitchen Layout where the equipment are to be installed is given in Annexure E.

The list of equipment with the specifications, makes and quantities is as below:

Item No.	Name of the Item	Specifications	Reference image	Approved makes and models	Qty
MK-18	Garbage can	80 litres capacity, overall size of unit shall be 500 mm dia x 790 mm high, heavy-duty seam-less construction, grey colour, with lids. Unit with castors & foot paddle to open lid.	 <p>PHOTO NOT CONTRACTUAL</p>	CAMBRO GMWBR8 OLGRY+G MFWB4G RY	4
MK-19	UNDER COUNTER REFRIGERATOR	Refrigerated cabinet- Overall size of the unit shall be 1721 mm wide x 710 mm deep x 800 mm high, mounted on 150 mm adjustable feet. Unit shall be Fully S.S Constructed with 60 mm thick High Density Polyurethane insulation. Unit shall be furnished with three doors, [Door hinges -1 left Door Hinge & 2 Doors Right Hinges.] Each Door section suitable to accommodate 3 nos of GN 1/1 Pans unit. Door's fitted with removable magnetic gaskets. All internal 90° corners shall be rounded. Temp of the unit shall range from -2 °C to +10°C to suit meat, fish and dairy storage requirements. Unit shall be suitable for operations in ambient temperatures of up to 43 °C. Forced air circulation for rapid cooling and an even temperature distribution. Completely automatic defrosting and automatic evaporation of defrost water by hot gas. Fully extractable cooling unit mounted on the left side, rated at 0.35 K.W., wired to operate on 220V.50C.1phase; Refrigerant gas used shall be CFC free [R-404A]. Unit shall be HACCP compliant.		Hoshizaki 436 ltrs	1






MK-24	COMBI OVEN WITH ACCESSORIES AND STAND	<p>Manual operation concept with 12 cooking modes: Soft Steaming 300 C – 990 C, Steaming 1000 C, Express Steaming: 1010 C up to 1300 C, Convection: 300 C up to 3000 C, Combi Steaming: 300 C up to 2500 C, Perfection: 300 C up to 1800 C. Low temperature cooking / Cook & Hold: 30°C up to 120°C, Delta-T cooking: Sous vide: Humidification: 30°C up to 220°C, Baking: 30°C up to 220°C. Capacity to hold GN 1/1 hanging rack with 6 inserts with tilt protection for containers. For 1/1 GN lengthwise insertion. Distance between insert levels: 60 mm. Body size 550 mm length x 783 mm depth x 758 mm High. Electrical heating rated at 7.8 KW, wired for operation on 415V-50C-3P, with power cord. Unit furnished with standard equipment. Door of the oven shall be right hinged. Unit shall be provided with Integral hand shower with automatic retracting system, integral water shut-off function.</p> <p>As optional accessories, unit to be furnished complete with</p> <ol style="list-style-type: none"> One set of 6-nos. S.S. GN 1/1 solid pans One set of 6-nos. S.S. GN 1/1 perforated pans. One set of 6-nos. of roast bake pans. Operational accessories. <p>ss stand for the unit to be provided.</p>		HOTMAX - GOURMET STAR2X 511 VISION ELECTRIC	1
MK-32	TWIN TANK DEEP FAT FRYER (COUNTER TOP)	<p>Counter top standing unit, Electrically heated; overall size of 590 mm Wide x 450 mm Deep x 320 mm High. Unit shall be fully Stainless steel with supporting structure constructed of S.S. Capacity of 2 X 8 litre tank. Each Basket size 220 mm wide x 260 mm deep x 100 mm high, over heating protection with safety thermostat. Total weight of unit - 15Kg.</p> <p>Features: 180°C operating thermostat; additional safety thermostat safety; micro switch to ensure correct positioning of element; heat resistant basket handles. Automatic oil filtering by decanting. Unit shall be provided with electrical pilot lights. Heating elements rated at 2 X 3.4K.W. total, wired to operate on 220V.50C.1Phase. Unit shall be furnished with power cord, lids and stand.</p>		SIRMAN - Eldorado 8X2 , 8X2 ltrElectric Table Top Double Tank Fryer	1






MK-42A	FIRE SUPPRESSION SYSTEM	<p>FIRE SUPPRESSION SYSTEM FOR HOOD ITEM NO. MK-42 (fabricated Island type Exhaust hood SIZE Boxed type profile of hood, 5700 mm long x 2700 mm deep x 600 mm) Automatic, water assisted wet chemical fire suppression system for protecting all grease producing cooking equipment, exhaust plenum & exhaust duct connection of exhaust hood Item # MK-42. Exhaust Hood od Size 5700 mm long x 2700 mm deep x 600 mm High. Unit fitted in a Stainless steel automan control panel of size 520 mm wide x 600 mm high x 195mm deep per control box. Pipe drops to discharge nozzles shall be stainless steel. Low PH liquid fire suppressant, Overlapping protection System capable of automatic [via fusible link] and manual actuation [a remote manual release to be located in the path of exit. Automatic Shut-down on Fuel supplies to be co-ordinate with others- such as Solenoid Valves for gas, Shunt-Shut for electrical fusible links to get activated at 3500 C. or as per recommendations. To be furnished complete with panel, detection & release system, chemical storage tank, sprinkler nozzles, S.S. piping & fittings. Contractor to submit shop drawing for obtaining approval from clients / consultant prior to supply. Scope of work shall include physical installation at site, dry run testing, training & handing over. Contractor shall be totally responsible to provide 100 % protections as required by local law and codes.</p>		ANSUL - Wall Type 3150mm x 1250mm	1
MK-45	UPRIGHT REACH IN REFRIGERATION	<p>Two half door vertical Chiller unit, capacity of 600 ltr. Unit mounted on four [4] nos. of 85 mm high counter type legs with adjustable in height up to 125 mm. Overall size of unit shall be [external] 720 mm wide x 780 mm deep x 1985 mm high. Fully S.S. constructed unit with S.S. 304. With 60 mm thickness, HCFC free, High density polyurethane insulation. Coated evaporator to avoid corrosion, reversible self-closing door with balloon profile, magnetic door seal, and rounded internal corners, door shall be hinged on left side. Temp of the unit shall range from -2 °C to +10 °C to suit meat, fish and dairy storage requirements. Lockable door with closure latch (included with optional locks). Door frame heater, activated according to external temperature, avoids condensation build-up around the door frame. Supplied with n. 4x2/1GN nylon coated grids and n. 4 sets of 2 stainless steel grid runners. Motor shall be rated at 1/3 HP. wired to operate on 220V.50C.1phase, Refrigerant gas used shall be CFC free [R-404A]. Unit shall be HACCP compliant.</p>		Hoshizaki - HRW 77 MS4 GN - Two Door Refrigerator; Cap : 628 Ltrs; Temp : -2 + 12 Deg C;Dim(mm)(wxdxh):700x818 x2050; With 150 legs; 4 Shelves; 4 sets of GN rails	1





MK-50	MOBILE INGREDIENT BIN	Each bin body of size 420mm Wide x 750mm deep x overall 710mm high inclusive of castors and Slant top with sliding lid with clear cover. One-piece seamless heavy-duty moulded polycarbonate bin with smooth covered interior corners. Bin of white color with a holding capacity of 102 Ltr. Unit provided with heavy-duty 3" Ø casters, 2-nos. swivel type & 2-nos. fixed type casters, bin lid of transparent slide back type, provided with S-hook for each, each bin to be furnished with 2-nos. plastic scoop.		CAMBRO -IBS27	1
MK-53	STORE ROOM SHELVING [DAY STORE]	Slotted angle shelving shall be arranged as per the layout plan inside the Kitchen Steward's Store Room. 1300 mm wide x 450 mm deep x 1850 mm high racks to be supplied, each rack provided with five [05] shelves, shelves of No.18 GA. Bito aluminum. Epoxy coated, as shown on plan with all sides turned down approx 1.1/2" & in 1/2" channel edges, corners of shelves bolted to 1.1/2" x 1.1/2" x No.16 GA Bito Aluminum. Epoxy coated vertical angle uprights of height 1850 mm each with nuts & bolts. Bottom of uprights provided with plastic insert feet. Each corner of adjoining shelves shall be bolted to common uprights angles with 4-sets of nuts & bolts. 1st shelf to be installed at 8" AFF, 2nd shelf installed 18" above 1st shelf, 5th shelf at top, with remaining 2-Nos. of shelves equally spaced in-between. Shelving Load Capacity 750 KG.		CAMBRO	1
MK-54	STORE ROOM SHELVING [DAY STORE]	Slotted angle shelving shall be arranged as per the layout plan inside the Kitchen Steward's Store Room. 1300 mm wide x 600 mm deep x 1850 mm high racks to be supplied, each rack provided with five [05] shelves, shelves of No.18 GA. Bito aluminum. Epoxy coated, as shown on plan with all sides turned down approx 1.1/2" & in 1/2" channel edges, corners of shelves bolted to 1.1/2" x 1.1/2" x No.16 GA Bito Aluminum. Epoxy coated vertical angle uprights of height 1850 mm each with nuts & bolts. Bottom of uprights provided with plastic insert feet. Each corner of adjoining shelves shall be bolted to common uprights angles with 4-sets of nuts & bolts. 1st shelf to be installed at 8" AFF, 2nd shelf installed 18" above 1st shelf, 5th shelf at top, with remaining 2-Nos. of shelves equally spaced in-between. Shelving Load Capacity 750 KG.		CAMBRO	2






MK-55	UPRIGHT REACH IN REFRIGERATOR –FOUR SECTION – S.S. SOLID DOORS	Four half door vertical chiller unit, capacity of 1300 ltr. Unit mounted on four [4] nos. of 85 mm high counter type legs with adjustable in height up to 125 mm. Overall size of unit shall be [external] 1440 mm wide x 780 mm deep x 1985 mm high. Fully S.S. constructed unit with S.S. 304. With 60 mm thickness, HCFC free, High density polyurethane insulation. Coated evaporator to avoid corrosion, reversible self-closing door with balloon profile, magnetic door seal, and rounded internal corners. Operating temperature shall be adjustable type from -2 to 10 °C to suit both meat and dairy storage requirements. Lockable door with closure latch (included with optional locks). Door frame heater, activated according to external temperature, avoids condensation build-up around the door frame. Supplied with n. 8x2/1GN nylon coated grids and n. 8 sets of 2 stainless steel grid runners. Motor shall be rated at 1/3 HP. wired to operate on 220V.50C.1phase, Refrigerant gas used shall be CFC free [R-404A]. Unit shall be HACCP compliant.		Hoshizaki - HRW 147 MS4 GN	1
MK-56	UPRIGHT REACH IN FREEZER–FOUR SECTION – S.S. SOLID DOORS	Four half door vertical chiller unit, capacity of 1300 ltr. Unit mounted on four [4] nos. of 85 mm high counter type legs with adjustable in height up to 125 mm. Overall size of unit shall be [external] 1440 mm wide x 780 mm dExecutive Education Block x 1985 mm high. Fully S.S. constructed unit with S.S. 304. With 60 mm thickness, HCFC free, High density polyurethane insulation. Coated evaporator to avoid corrosion, reversible self-closing door with balloon profile, magnetic door seal, and rounded internal corners. Operating temperature shall be adjustable type from -18 to -20 °C to suit both meat and dairy storage requirements. Lockable door with closure latch (included with optional locks). Door frame heater, activated according to external temperature, avoids condensation build-up around the door frame. Supplied with n. 8x2/1GN nylon coated grids and n. 8 sets of 2 stainless steel grid runners. Motor shall be rated at 1/3 HP. wired to operate on 220V.50C.1phase, Refrigerant gas used shall be CFC free [R-404A]. Unit shall be HACCP compliant.		Hoshizaki	1
MK-57	CHEST FREEZER CABINET	Free standing, horizontal ice cream freezer cabinet, of size 1116 mm wide X 604 mm dExecutive Education Block X 845 mm high on castors, with one nos. of solid top door [lockable]. Unit furnished with one [1] no. of basket. Volume of tank shall be 302 liters, temperature of unit shall be -18O C. Unit wired to operate on 220V.50C.1P. Unit furnished with power cord.		Bluestar - CHFSD30 OD	1






MK-65	INSECT-O-CUTTERS WITH GUM PAD	PCI - Spider with Standard tube Spider, Control Board Sets. (15 Nos. Sheets)		PCI	1
MD-04	PRE-RINSE SPRAY UNIT [DECK MOUNTED]	Unit shall be 8" deck mount mixing faucet with polished chrome plated brass body, add-on faucet with compression cartridge and lever handle, 8" swing nozzle with stream regulator outlet, 24" riser, 44" flexible stainless steel hose with heat resistant handle, 1.42 GPM spray valve with insulated grip handle, compression cartridges with spring checks, lever handles, 1/2" NPT female inlets, spray valve holder, 6" adjustable wall bracket and overhead spring. Unit shall be suitable to sustain, Pressure: 20 - 125 psi, suitable for incoming temp of Temperature: 40 F - 140 F. Flow rate for the spray valve shall be 1.42 GPM@60PSI and 6.49 GPM @ 60 PSI.		T&S B-0123-ADF08-B EX-1DP00-H	1



MD-05	HOOD TYPE DISH / GLASS WASHING MACHINE [CORNER TYPE INSTALLATION]	Free Standing, suitable for warm water operation, Single-tank machine with circulation wash water and fresh water rinsing, automatic warm water inlet, fully automatic dishwashing machine with a washing capacity of 30 racks per hour. Overall dimensions shall be 635 mm wide X 750 mm dExecutive Education Block X 1475 mm high [closed door] & 2050 mm high with door in open position, with clear entry height shall be 440 mm and working height of the unit shall be 850 mm. Suitable for 500 X 500 rack size. fully S.S constructed. Rising pipes, filtration system, wash unit inclusive of wash jets and filter cartridge shall be manufactured from particularly durable and recyclable Polypropylene. Tank shall be constructed of one piece without corners [dExecutive Education Block drawn tank] with heated integrated into the outside of the tank to prevent dirt deposits. The hood shall be fitted with a safety limit switch. The machine shall be double-skinned insulation in the tank area, back wall machine casing and closed bottom tray. Overall capacity of the wash tank shall be 22 litres. Unit shall be equipped with rinse aid pump, pumped directly from the chemical container via a suction pipe. Total connected load of unit shall be 9.6 KW, wired to operate on 440V- 50C.3Phase, with hot water supply connection. Unit shall be furnished with the Following Standard accessories, 1 plate rack, 8-divisions, 1 plate, cup & Cutlery rack, Plastic coated wire rack incl. rack angles, 1 flexible water inlet hose, 1 flexible water drainage hose, 1 electric connection cable. As extra accessories, following dish racks to be supplied along with the machine: 1. Two [2] nos. open pocket cutlery racks.		HOBART - Ecomax H604	1
MG-01	WET MASALA GRINDER [TILTING TYPE]	Capacity 10 liter per charge, of size 600 mm [W] X 750 mm [D] X 1270 mm [H] motor rated at 2.0 HP, to operate on 220V-50C-1Phase furnished with power cord, grinding cycle of 45 minutes, S.S. drum & base cladding, mounted on S.S. legs frame work, with optional coconut scraper & power cord etc.		Sowbhagya / COSMOS	1
MD-17	WALL MOUNTED FLUSHING HOSE UNIT WITH SWING, Hose reel bracket, channel	Open epoxy coated hose reel assembly Stainless Steel Hose Reel, Unit shall be provided with a single 3/8" female inlet & adjustable hose bumper. Unit shall be S.S. constructed with w/ Rear Trigger 5/16" Orifice Spray Gun, Suitable for mounting on wall. Hose of the unit shall be 50' long, mounting hardware / trigger gun. Unit shall be supplied with epoxy coated black swing bracket for fits 3/8" X 50' & all 1/2" hose reels. Unit shall also provided with spray valve [B-0107].		T&S 5HR-232-01	1



AE-01	Idli Steamer	Capacity - to steam 200 idlis at a time Stainless steel construction Gas based			1
AE-02	Stone Grinder	Electric Stone grinder for making batters; Tilting type ; 10 ltrs			1
FD-18	DUNNAGE RACKS [FOOD STORE]	Size of each unit to be 1200 mm wide X 650 mm dExecutive Education Block X 130 mm high. Unit shall be injection moulded, steel reinforced flat pallet, compatible with all existing lifting systems, easy to clean & wash, excellent resistance to most chemicals, maintenance free, rot proof, secure, robust design to render long service, meets all GMP requirements, hygienic, water proof, high impact strength and rigidity.		NEELKAM AL - SP1210M W	5

Note: -

1. The selected vendor will be responsible for Supply, installation & testing of the equipment at IIM Nagpur MIHAN campus.
2. The delivery will be completed within 4 weeks of the issue of order.
3. The vendor will plan the installation of the equipment with the institute authorities and deploy sufficient manpower for the same.
4. The vendor will be responsible for coordinating with after-sales installation team of the product manufacturers.
5. Minimum 1-year warranty is required on all Products which is further extendable. The user manual and warranty certificates will be handed over to IIM Nagpur authority after installation and testing.
6. The vendor will support IIM Nagpur for any after sales service requirements.



PARTICULARS OF BIDDER

SR.NO	DESCRIPTION	
1	Name of the bidder	
A	Trade Name (in Block letters)	
B	Status of the Bidder (Proprietorship/Partnership/LLP/Limited Co.) In Block letters)	
2	Postal Address for communication	
3	Telephone No.	
4	E-mail / Website address (if available)	
5	PAN (Enclose self-attested photocopy)	
6	GSTIN (GST Registration No.) (If applicable) (Enclose self-attested photocopy)	

I/We hereby declare and affirm that I/we have read and understood the terms and conditions of this tender/quotation/NIT as stipulated in the tender notice No IIMN/113/2022-23/007 Dated 08/04/2022. Accordingly, I/ we accept the terms and conditions and hereby offer the rates for **“Supply Installation and commissioning of Kitchen Equipment for EXECUTIVE EDUCATION BLOCK Dining for IIM Nagpur MIHAN Campus as per Price Bid.**

Signature _____

Date_____

Official seal of bidder_____



Annexure B

FORMAT OF BID SECURITY DECLARATION FROM BIDDERS IN LIEU OF EMD
(On Bidder's Letter head)

I / We, the authorized signatory of M/s..... , participating in the tender No. IIMN/113/2022-23/007 dated 08/04/2022 for **Supply Installation and commissioning of Kitchen Equipment's for EXECUTIVE EDUCATION BLOCK Dining for IIM Nagpur MIHAN Campus**, do hereby declare:

- (i) That I / we have availed the benefit of waiver of EMD while submitting our offer against the subject Tender and no EMD is being deposited for the said tender.
- (ii) That in the event we withdraw / modify our bid during the period of bid validity Or I/we fail to execute formal contract agreement within the given timeline OR I/we fail to submit a Performance Security within the given timeline Or I/we commit any breach of Tender Conditions / Contract which attracts penal action of forfeiture of EMD

Then I/we will be suspended from being eligible for bidding / award of all future contract(s) of Indian Institute of Management Nagpur for a period of one year from the date of committing such breach.

Signature of Authorized Signatory of bidder

Name of Authorized Signatory

Company Name



Sr.no	Year	Annual turnover	Profit & loss
1	2018-19		
2	2019-20		
3	2020-21		

Signature _____

Date _____

Official seal of bidder _____



Annexure D

Technical Bid

Please fill in the proposed products brands and models with specifications (as per scope of work Chapter 3) for which the rates are quoted in the Price Bid. Please **DO NOT** quote rates here.

Item.No.	Item	Brand & Model	Specifications as per Scope of Work (Yes / No)
MK-18			
MK-19			
MK-24			
MK-32			
MK-42A			
MK-45			
MK-50			
MK-53			
MK-54			
MK-55			
MK-56			
MK-57			
MK-65			
MD-04			
MD-05			
MG-01			
MD-17			
AE-01			
AE-02			
FD-18			

I/We hereby declare and affirm that I/we have read and understood the scope of work as per Chapter 3 of the tender notice No IIMN/113/2022-23/007 Dated 08/04/2022. Accordingly, I/ we hereby offer the above products and the rates for the same are quoted in the Price Bid.

Signature _____

Date _____

Official seal of bidder _____



CHECK LIST OF DOCUMENTS TO BE SUBMITTED

Bidder is required to fill-up this checklist and submit with the PQ and Technical bid:

Sr.no	Description	Compliance YES/NO / Document attached	Bid document Reference
1	Particulars of bidders (Annexure A)		
2	Bid security declaration (Annexure B)		
3	PAN		
4	GST Registration		
5	Proof of authorized dealership		
6	Proof of bidder as per Eligibility criteria Chapter 2		
7	The annual turnover of the firm in last three consecutive financial years as on 31.03.2020 (For FY 2017-18, 2018-19 & 2019-20) shall be minimum Rs: 25 lakh Annexure C		
8	Annexure D Technical Bid		
9	Undertaking – Not blacklisted from any government organization		



**Chapter -4
 Price Bid**

**Tender No: IIMN/113/2022-23/007 dated 08/04/2022
 (To be submitted in separate envelope)**

NAME OF WORK: Tender for Supply Installation and commissioning of Kitchen Equipment for EXECUTIVE EDUCATION BLOCK Dining for IIM Nagpur MIHAN Campus.

Enter the Bidder's Name						
Sr.no	Item Name	Brand, Model (As quoted in technical Bid)	Quantity	GST %	Rate Including GST (in figures)	Amount (Rate x Quantity)
MK-18	Garbage can		4			
MK-19	UNDER COUNTER REFRIGERATOR		1			
MK-24	COMBI OVEN WITH ACCESSORIES AND STAND		1			
MK-32	TWIN TANK DEEP FAT FRYER (COUNTER TOP)		1			
MK-42A	FIRE SUPPRESSION SYSTEM		1			
MK-45	UPRIGHT REACH IN REFERIGATION		1			
MK-50	MOBILE INGREDIENT BIN		1			
MK-53	STORE ROOM SHELVING [DAY STORE]		1			
MK-54	STORE ROOM SHELVING [DAY STORE]		2			
MK-55	UPRIGHT REACH IN REFRIGERATOR – FOUR SECTION		1			



MK-56	UPRIGHT REACH IN FREEZER-FOUR SECTION		1			
MK-57	CHEST FREEZER CABINET		1			
MK-65	INSECT-O-CUTTERS WITH GUM PAD		1			
MD-04	PRE-RINSE SPRAY UNIT [DECK MOUNTED]		1			
MD-05	HOOD TYPE DISH / GLASS WASHING MACHINE [CORNER TYPE INSTALLATION]		1			
MG-01	WET MASALA GRINDER [TILTING TYPE]		1			
MD-17	WALL MOUNTED FLUSHING HOSE UNIT		1			
AE-01	Idli Steamer		1			
AE-02	Stone Grinder		1			
FD-18	DUNNAGE RACKS [FOOD STORE]		5			
Total Amount including Freight/Transit Insurance/Installation and all Taxes:						

Total Amount in words (including GST) - _____

Name of Bidder -
Signature -
Seal -